

Manufacturer

Catalog Number

c - Bolts, machine

	<u>5/8"</u>	<u>3/4"</u>
Chance	C88XX(1)	C89XX(2)
Joslyn	J88XX(6)	J89XX(7)

ao - Bolts, straight, thimble-eye

	<u>5/8"</u>	<u>3/4"</u>
Chance	C55XX(3)	C56XX(4)
Joslyn	J80XX(8)	J80XX(9)

ba - Bolts, angle, thimble-eye

	<u>5/8"</u>	<u>3/4"</u>
Chance	C50XX(3)	C51XX(5)
Joslyn	J81XX(8)	J81XX(9)

See page 7.13.1 for notes.

7.13.1
1-03
c;ao;ba

Notes:

- (1) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20", 22", and 24".
- (2) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 8", 10", 12", 14", 16", 18", 20", 22", 24", and 26".
- (3) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 10", 12", 14", and 16".
- (4) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 12" and 14".
- (5) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 10", 12", and 14".
- (6) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 11", 12", 13", 14", 15", 16", 18", 20", 22", and 24".
- (7) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 5", 6", 7", 8", 9", 10", 12", 14", 16", 18", 20", 22", 24", and 26".
- (8) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 6", 8", 10", and 12".
- (9) Order bolts by changing X's in catalog number to length of bolt in inches; accepted for lengths 8", 10", and 12".